

EXTENSION FOR ROOF CONVEYOR

[0001] The present invention relates generally to conveyors. More particularly, the present invention relates to platform extensions for conveyors that extend and/or rotate from an end of the conveyor and aid the person unloading the conveyor.

BACKGROUND OF THE INVENTION

[0002] Many types of conveyors are widely known in the art. Conveyors typically comprise a fixed or articulated frame member, or boom, with an endless conveyor belt or chain located about the boom. Conveyors are generally used to transport materials, such as bundles of shingles and other roofing materials from, *i.e.*, a truck to a roof top. Another form of conveyor system that may be utilized in conjunction with the present invention is a latter truck, such as the latter trucks used by fire departments.

[0003] One inherent problem with conveyors involves the angle of the conveyor in relation to an upper surface, such as a roof. This problem is especially evident when transporting, *e.g.*, shingles onto a residential housing roof or other pitched surface. Since the conveyor is angled upwardly when transporting materials, the end of the conveyor may be vertically-spaced from the roof surface. As such, the person unloading the conveyor may have to reach above his or her head to receive the materials carried by the conveyor. Additionally, pitched roofs render a person's footing unsafe, especially when removing heavy items from the conveyor.

[0004] There is a need for a conveyor that provides a more level and safer approach angle for the person unloading materials from the conveyor. Accordingly, the present invention is hereby submitted.

SUMMARY OF THE INVENTION

[0005] One advantage of the present invention is realized by providing a conveyor having a platform or plank extendible from one end of the conveyor.

[0006] Another advantage of the present invention is realized by providing a conveyor having a platform or plank that is selectively rotatable or pivotable from the main boom of the conveyor.

[0007] These and other advantages of the present invention are realized by providing a conveyor for transporting materials from a first location to a second location that comprises an elongated boom having a first end, a second end, a top surface, and a bottom surface; a conveyor mechanism such as an endless belt or chain that is operably attached to the elongated boom; and a plank or platform operably attached to the boom adjacent to the bottom surface of the boom, wherein the platform is selectively pivotable from the boom and capable of providing a walking surface for the person unloading the conveyor. The platform may additionally or alternatively be at least partially extendible from one end of the elongated boom. The platform may be attached to a platform support, with the platform support being slidably or rollably attached to the elongated boom.

SUMMARY OF THE DRAWINGS

[0008] FIG. 1 is a perspective view of a conveyor with an extendible and pivotable platform, in accordance with a preferred embodiment of the present invention.

[0009] FIG. 2 is a perspective view of the conveyor of FIG. 1, shown with the platform and platform support detached from the boom

[0010] FIG. 3 is a perspective view of the conveyor of FIG. 1 attached to a vehicle and with the platform extended and pivoted downwardly.

[0011] FIG. 4 is a side schematic view of the conveyor of FIG. 1.

[0012] FIG. 5 is a perspective view of a second embodiment of a conveyor with a platform support track.

[0013] FIG. 6 is a close-up perspective view of a portion of the conveyor of FIG. 4, showing the platform support track and a hydraulic cylinder for actuation of the platform.

[0014] FIG. 7 is a close-up perspective view of a portion of the conveyor of FIG. 4, showing a pivotable connection of the platform and a roller on the platform support track.

DETAILED DESCRIPTION OF THE INVENTION

[0015] A preferred embodiment of a conveyor 10 is illustrated in Figure 1. The conveyor 10 comprises a main boom 12 and conveyor mechanism 28, 128, such as a belt or chain. The main boom 12 comprises a first end 14 and a second end 16, and is attached to a base support. Preferably, the conveyor 10 comprises means for adjusting the pitch of the main boom 12 vertically and for translating the main boom 12 radially or horizontally. In a preferred

embodiment, a rotatable pedestal 24 of a type known in the art is attached near the first end 14 to a base support. The rotatable pedestal 24 provides radial movement of the main boom 12. Rotatable pedestal 24 also preferably includes at least one hydraulic actuator 22 that facilitates movement of the main boom 12 vertically. As such, the main boom 12 is preferably adjustable both vertically and horizontally. The controls for the rotatable pedestal 24 and hydraulic actuator 22 are both of a type generally known in the art.

[0016] The main boom 12 additionally comprises upper or top surface 18 and lower or bottom surface 20. An endless conveyor mechanism 28, such as a belt, chain, or other structure known in the art may be operably attached to the main boom 12, such that materials to be transported are loaded onto the upper surface 18 of the main boom 12 near the first end 14. The materials are then conveyed toward the second end 16 of the main boom 12 and are unloaded accordingly. It is also contemplated that the main boom 12 may comprise a ladder device with rungs 128 in lieu of an endless conveyor mechanism 28.

[0017] Referring now to Figure 2, the conveyor 10 further comprises platform 30, which may be extendable from the second end 16 and/or rotatable or pivotable downward from the main boom 12. Preferably, the platform 30 is of sufficient width to enable a person to walk across it. Additionally, the platform is preferably constructed of a rigid material such as steel or aluminum alloy, although any sufficiently rigid material can be utilized without deviating from the scope of the present invention.

[0018] The platform 30 is preferably pivotally attached at one end to a platform support, which in FIG. 2 is illustrated as carriage 40. The carriage 40 is preferably rollably or slidably attached to the main boom 12. In a preferred embodiment, the carriage 40 comprises inwardly-

projecting flanges 42 that forms slots 44. Slots 44 receive outwardly-projecting flanges 26 on main boom 12. In such an embodiment, carriage 40 is slidably attached to boom 12. Alternatively, a plurality of rollers could be utilized instead of flanges 26, without deviating from the scope of the present invention. It is also contemplated that the carriage 40 may be fixed in relation to the boom, with the platform 30 being telescopically extendable.

[0019] The platform 30 is preferably rotatably attached to carriage 40 at or near one end of the platform 30, such that the platform is selectively pivotable downward. As such, the user can position the platform 30 to provide a more level walking surface for the person or persons approaching the main boom 12 to unload materials from the conveyor 10. Any rotatable connection as is known in the art may be utilized. A preferred embodiment for the rotatable connection comprises pins or rods 48 that are received in apertures (not shown) in the carriage 40. To facilitate rotation of the platform 30, a hydraulic actuator 46 may be attached to the carriage 40 on one end and to the underside of the platform on the other end, as illustrated in FIG. 2. In such an embodiment, retraction of the hydraulic actuator 46 causes downward rotation of the platform 30. In the same manner, extension of the hydraulic actuator 46 causes the platform to rotate upwardly back to a position substantially parallel to main boom 12.

[0020] Rather than carriage 40, it is also contemplated that the platform 30 may be slidably or rollably attached to the main boom by any suitable platform support as is known in the art, without deviating from the scope of the present invention. For example, the platform 30 may be supported by cage or track 126 and slidably or rollably extendible and retractable from the cage or track 126. In such an embodiment, illustrated in FIG. 6, the platform 30 may be rotatably attached to a drive member 50, such that after a predetermined critical distance of extension,

when the joint between the platform and the drive member approaches the end of the cage or track 126, the platform passively rotates downwardly.

[0021] Additionally, the platform 30 may be slidably or rollably attached to an elongated support member attached to the main boom 12, such that the platform 30 is extendible and retractable along the length of the support member but not rotatable in relation to the support member. In such an embodiment, the support member, itself may be rotatable downwardly to adjust the angle of the platform 30.

[0022] Extension and retraction of platform 30 is preferably hydraulically actuated. For example, carriage 40 may be translatable longitudinally in relation to the main boom 12 via opposing hydraulic winches 60 (FIG. 7) located at or near the ends of the main boom 12. To translate the platform 30, one winch 60 would wind its cable, while the opposing winch unwinds its cable. Alternatively, the hydraulic actuator may be a hydraulic cylinder 52 having its longitudinal axis substantially parallel to the main boom 12. Alternatively, extension and retraction of the platform 30 may be any other chain or winch drive as is known in the art. For example, opposing sides of the carriage 40 may be attached to chains or cables or the like. The chains or cables may additionally be attached to rotatable spools or drums, powered by any means known in the art, such that by winding the cable around one drum, while simultaneously unwinding the cable from the second drum translates the platform 30 forward or backward in relation to the main boom 12.

[0023] Optionally, platform 30 may further comprise at least one stabilizing member or leg 38. Stabilizing member 38 is preferably adjustable or rotatable downwardly in relation to

platform 30. Optional stabilizing leg 38 may be used, for example, when only one side of the platform is touching a surface such as a roof.

[0024] In operation, the user first adjusts the elevation and direction of conveyor 10. The conveyor can either be fixed, manually moveable, or attached to a vehicle 70. After the elevation and direction of the conveyor 10 is selected, the user subsequently extends the platform 30 from the main boom 12 a predetermined distance, preferably via a hydraulic winch 60, hydraulic cylinder 52, or other chain or cable drive. After the platform 30 extends from the main boom 12 a predetermined distance, the user next rotates the platform 30 downwardly, with the end of the platform 30 resting on, if possible, a roof or other upper surface. It should be understood that if the platform 30 is extendible from a rotatable platform support, the user would rotate the platform support, itself, either before or after extension of the platform 30. Additionally, if the platform 30 is passively rotatable downwardly after extension a predetermined distance, the user only needs to extend the platform a predetermined distance to facilitate its rotation downwardly.

[0025] If the platform 30 is angled such that only one side of the platform 30 is touching the roof, optional support leg 38 can be engaged downwardly to ensure that both sides of the platform 30 are supported by the roof.

[0026] The forgoing disclosure is illustrative of the present invention and is not to be construed as limiting thereof. Although one or more embodiments of the invention have been described, persons of ordinary skill in the art will readily appreciate that numerous modifications could be made without departing from the scope and spirit of the disclosed invention. As such, it should be understood that all such modifications are intended to be included within the scope of

this invention. The written description and drawings illustrate the present invention and are not to be construed as limited to the specific embodiments disclosed.